

**GOBLE**

Serial No. 10/036,500

**AMENDMENTS TO THE CLAIMS**

1. (Withdrawn)
2. (Withdrawn)
3. (Withdrawn)
4. (Withdrawn)
5. (Withdrawn)
6. (Withdrawn)
7. (Withdrawn)
8. (Withdrawn)
9. (Withdrawn)
10. (Withdrawn)
11. (Withdrawn)
12. (Withdrawn)
13. (Withdrawn)
14. (Withdrawn)
15. (Withdrawn)
16. (Withdrawn)
17. (Withdrawn)
18. (Withdrawn)
19. (Withdrawn)
20. (Withdrawn)

**GOBLE**

Serial No. 10/036,500

21. (Withdrawn)

22. (Withdrawn)

23. (Withdrawn)

24. (Withdrawn)

25. (Withdrawn)

26. (Withdrawn)

27. (Withdrawn)

28. (Withdrawn)

29. (Withdrawn)

30. (Withdrawn)

31. (Currently amended) A method of treating a tumour in a colon using an electrosurgical system comprising:

an electrosurgical generator adapted to generate a radio frequency oscillating voltage output across first and second output terminals;

an electrosurgical instrument having an active tissue treatment electrode connected to the first generator output terminal;

fluid delivery means for delivering electrically-conductive fluid to the tumour to be treated; and

a return electrode connected to the second generator output terminal,

the method comprising the steps of:

enclosing, in a substantially fluid-tight manner, a space in the colon within

**GOBLE**

Serial No. 10/036,500

which the tumour to be treated is located, and within which ~~at least~~ the active electrode is located;

operating the fluid delivery means at least partly to fill the space with electrically-conductive fluid;

positioning the return electrode within the space;

operating the generator to apply a radio frequency voltage between the active and return electrodes, and completing at least a part of a conduction path between the active and return electrodes using the electrically-conductive fluid; and

manipulating the active electrode in the vicinity of the tumour to be treated to vaporise the tumour.

32. (Canceled)

33. (Canceled)

34. (Currently amended) A method of treating a tumour in a colon using an electrosurgical system comprising:

an electrosurgical generator adapted to generate a radio frequency oscillating voltage output across first and second output terminals;

an electrosurgical instrument having an active tissue treatment electrode connected to the first generator output terminal;

fluid delivery means for delivering electrically-conductive fluid to the tumour to be

treated; and

a return electrode connected to the second generator output terminal,

the method comprising the steps of:

enclosing, in a substantially fluid-tight manner, a space in the colon within which the tumour to be treated is located, and within which ~~at least~~ the active electrode is located;

operating the fluid delivery means at least partly to fill the space with electrically-conductive fluid;

operating the generator to apply a radio frequency voltage between the active and return electrodes, and completing at least a part of a conduction path between the active and return electrodes using the electrically-conductive fluid; and

manipulating the active electrode in the vicinity of the tumour to be treated to vaporise the tumour; and

wherein the electrosurgical instrument comprises a shaft, and the active and return electrodes are located on a distal end of the shaft, whereby the return electrode is located within the space with the active electrode, the method further comprising the steps of positioning the proximal end of the shaft to extend out of the space, and manipulating the active electrode by moving the proximal end of the shaft.

35. (Original) A method according to claim 31, wherein the electrically-conductive fluid is supplied to the space continually, and the method further comprises the step of removing waste matter from within the space.

**GOBLE**

Serial No. 10/036,500

36. (Original) A method according to claim 31, wherein the electrically-conductive fluid is a gas.

37. (Currently amended) A method ~~according to claim 31, of treating a tumour~~  
in a colon using an electrosurgical system comprising:

an electrosurgical generator adapted to generate a radio frequency oscillating voltage output across first and second output terminals;

an electrosurgical instrument having an active tissue treatment electrode connected to the first generator output terminal;

fluid delivery means for delivering electrically-conductive fluid to the tumour to be treated; and

a return electrode connected to the second generator output terminal,

the method comprising the steps of:

enclosing, in a substantially fluid-tight manner, a space in the colon within which the tumour to be treated is located, and within which at least the active electrode is located;

operating the fluid delivery means at least partly to fill the space with electrically-conductive fluid;

operating the generator to apply a radio frequency voltage between the active and return electrodes, and completing at least a part of a conduction path between the active and return electrodes using the electrically-conductive fluid; and

manipulating the active electrode in the vicinity of the tumour to be treated;

wherein the space is enclosed by means of a flexible enclosing member which forms a seal with a portion of the colon.

38. (Original) A method according to claim 37, wherein the method further comprises the step of reducing the pressure within the space to a level below air pressure in the immediate vicinity outside the space.

39. (Previously presented) A method of treating a tumour in a colon using an electrosurgical system comprising:

an electrosurgical generator adapted to generate a radio frequency oscillating voltage output across first and second output terminals;

an electrosurgical instrument having an active tissue treatment electrode connected to the first generator output terminal;

fluid delivery means for delivering electrically-conductive fluid to the tumour to be treated; and

a return electrode connected to the second generator output terminal,

the method comprising the steps of:

enclosing, in a substantially fluid-tight manner, a space in the colon within which the tumour to be treated is located, and within which at least the active electrode is located;

operating the fluid delivery means at least partly to fill the space with electrically-conductive fluid;

operating the generator to apply a radio frequency voltage between the active and return electrodes, and completing at least a part of a conduction path between the active and return electrodes using the electrically-conductive fluid; and manipulating the active electrode in the vicinity of the tumour to be treated;

wherein the space is enclosed by means of a flexible enclosing member which forms a seal with a portion of the colon; and

wherein the flexible enclosing member includes a proximal bung and a distal bung.

40. (Original) A method according to claim 39, including the further step of inflating the colon by delivering conductive fluid to the space through a first opening in the distal bung so that the tumour can be treated by the active electrode.

41. (Original) A method according to claim 40, including the further step of inserting into the space through the first opening an endoscope having a first channel for delivering the conductive fluid and a second channel for inserting the active electrode.

42. (Original) A method according to claim 40, including the further step of removing the conductive fluid from the space through a second opening in the proximal bung.

43. (Original) A method according to claim 37, wherein the flexible enclosing member is inserted endoscopically into the space through the colon's lumen.

44. (Previously presented) A method of -treating a tumour in a colon using an electrosurgical system comprising:

an electrosurgical generator adapted to generate a radio frequency oscillating voltage output across first and second output terminals;

an electrosurgical instrument having an active tissue treatment electrode connected to the first generator output terminal;

fluid delivery means for delivering electrically-conductive fluid to the tumour to be treated; and

a return electrode connected to the second generator output terminal,

the method comprising the steps of:

enclosing, in a substantially fluid-tight manner, a space in the colon within which the tumour to be treated is located, and within which at least the active electrode is located;

operating the fluid delivery means at least partly to fill the space with electrically-conductive fluid, the space being enclosed by means of a flexible enclosing member which forms a seal with a portion of the colon;

operating the generator to apply a radio frequency voltage between the active and return electrodes, and completing at least a part of a conduction path



between the active and return electrodes using the electrically-conductive fluid; and  
manipulating the active electrode in the vicinity of the tumour to be  
treated; and

laparoscopically inserting a flexible sleeve to thereby surround a region of  
the colon containing the tumour to be treated and apply a second pressure against a  
first pressure resulting from the filling of the space with the electrically-conductive fluid.

45. (Original) A method according to claim 44, wherein the flexible enclosing  
member includes a proximal bung and a distal bung and wherein the proximal and  
distal bungs form a pressure seal against both the colon and the pressure applied via  
the inflatable sleeve.

46. (Original) A method according to claim 44, wherein the active electrode is  
manipulated to remove the tumour and a region of the colon within which the tumour is  
located once the blood supply and lymphatics of the region have been disconnected.

47. (Original) A method according to claim 40, including the further step of  
inserting into the space through the first opening an endoscope having a fluid channel  
for delivering the conductive fluid and an instrument channel for inserting the active  
electrode.